## NV-KIT830W-4CAM-1TB

Nivian WiFi CCTV kit

NVR 8 channels

4 cameras 3 Pre-registered Mpx

Additional cameras NV-CAM30W

1 HDD 1TB included

Esaecloud App and Software



Nivian

WiFi video surveillance kit

Contains

1 x 8-channels NVR

4 Cameras 3Mpx 4mm IR 20 m for outdoor IP66

Expandable: Additional cameras NV-CAM30W

WiFi connection or Ethernet network between NVR and cameras

WiFi or Ethernet network connection between NVR and router

Wide WiFi range 2.4 GHz (700 m in open space)

WiFi repeater function on each camera

Compression H.265+

Full HD HDMI and VGA Output

Continuous/Programmed Recording/Motion Detection

Included Hard Disk 1TB specific for video surveillance

Installation Plug&Play (Preconfigured cameras)

Included feeders

Remote access by Web browser, PC/Mac software and Eseecloud App (IP PRO)  $\,$ 

## Specifications

## IP cameras

Image sensor	1/3" 3 Megapixel Progressive Scan Sensor
Main Resolution	2304x1296 (15 FPS)
Secondary resolution	640x360 (15 FPS)
Compression	H.265+ / H.264+
Lens	4 mm (D: 104°)
Minimum illumination	0 Lux / 3 IR LEDs (20 m)
Network interface	Ethernet 10/100 BaseT (100 m) and Wifi 2.4 GHz 802.11b/g/n (700 m open space)
Plug&Play access	Preregistered in the NVR-wifi
Image improvements	3D-DNR, BLC, Mirror Vision V/H, Privacy Mask
ENVIRONMENT	Suitable for outdoor use IP66, lightning protection 4000V
Operating temperature	-20° C ~ 50° C
Power	DC 12 V / 1 A (included)
Dimensions / Weight	66 (Al) x 66 (An) x 180(Fo) mm / 500 g
NVR	
Inputs for IP cameras	LAN / WiFi port up to 8 channels
Supported resolutions	5Mpx / 3Mpx / 1080p / 960p / 720p
Supported video compression format	H.265+ / H.265 / H.264
Video outputs	1 HDMI Full HD, 1 VGA
Resolution HDMI/VGA display	1920x1080, 1440x900, 1280x1024, 1024x768
Simultaneous display	4Ch@3Mpx or 2Ch@5Mpx, Intelligent resolution adaptation
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Recording method	Manual, programmed, motion detection
Internal memory	1 SATA HDD 3.5" up to 6 TB (1 HDD 1TB included)
Communication	1 USB (shared mouse and backup) / 1 RJ45 (Ethernet) / WiFi (AP and client)
Remote access	EsaeCloud Web Browser, Software and App (IP PRO)
Power	DC 12 V / 2 A (included)
Dimensions	42 (H) x 258 (W) x 210 (D) mm