

IP CCTV / Professional IP cameras / Uniview - Uniarch / Bullet Cameras

UV-IPC2128LB-ADF28K-G

Uniview



Features

- IP Bullet Camera - Easy Range
- 8 MP (3840x2160)
- 2.8 mm Lens
- Minimum illumination 0.01 lux | 0 lux with supplemental light
- IR range of 30 m
- SIP (Smart Intrusion Prevention) Lite: combines artificial intelligence algorithms with real-time video analysis to accurately identify human and vehicular intrusions, minimizing false alarms caused by animal movements or weather conditions
- UMD (Ultra Motion Detection): thanks to its advanced AI algorithm, UMD is able to detect changes in the environment extremely efficiently, even in conditions of high speed or motion difficult to capture by other technologies
- WDR 120 dB
- Integrated microphone
- Slot for MicroSD card up to 512 GB
- PoE
- IP67
- Corridor mode 9:16
- Metal and plastic
- ONVIF Compatible

Specifications

Brand	Uniview
Range	Easy Basic
Image sensor	1/2.7" Progressive Scan CMOS
Maximum resolution	8 Megapixel (3840x2160)
Main Stream rate	8MP (3840*2160)@15fps; 5MP (2880*1620)@25/20fps ;4MP (2560*1440)@25/20fps; 3MP (2304*1296)@30/25fps; 2MP (1920*1080)@30/25fps
Extra Stream rate	720P (1280*720)@30/25fps; D1 (720*576), Max 30fps; 640*360,Max 30fps
Compression	Ultra265/H.265/H.264
Lens	2.8 mm
Range performance	Detect 63 m Observe 25.2 m Recognize 12.6 m Identify 6.3 m
FOV	107° (H), 59.7° (V), 111.5° (D)
Minimum illumination	0.01 Lux (Colour)
Infrared range	30 m
Image improvements	WDR 120 dB, BLC, HLC, AGC, 2D/3D-NR, Motion detection, ROI, Privacy Mask
Intelligent functions	Line Crossing, Intrusion, Anti-Tampering
UMD	Support Motion detection based on human body detection
SIP (Smart Intrusion Prevention) Lite	Support Line crossing and intrusion based on human body detection
Day / Night	Mechanical ICR filter
Internal memory	MicroSD card, Max 512 GB
Alarms	Does not have
Audio	Built-in microphone
Remote access	Web Browser, CMS Software (EZStation), Smartphone (EZView/EZLive)
Interoperability	ONVIF
Power	DC 12V / 5W PoE (IEEE802.3af)

Temp. operation	-30° C ~ 60° C
Degree of protection	Weatherproof IP67 Overvoltage 4000 V
Dimensions	161 (H) x 62 (W) x 63 (D) mm
Weight	330 g