

IP CCTV / Professional NVRs / Uniview - Uniarch

UV-NVR301-04S3-P4

Uniview



Features

- Uniview
- NVR for IP cameras
- Easy range
- 4 CH
- 64 Mbps bandwidth supported
- Maximum resolution 8 Megapixel
- Compression Ultra265/H.265/H.264
- Audio output
- VGA and HDMI 4K output
- Corridor mode
- Mouse
- Space for 1 HDD up to 6 TB
- 4 PoE ports IEEE802.3af/at
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

Specifications

Brand	Uniview
Range	Easy
Inputs for IP cameras	LAN port up to 4 channels
Power over Ethernet	4 PoE IEEE802.3at(max.54 port switch W)
IP compatible cameras	UNIVIEW, ONVIF
Bidirectional audio	1 RCA output
Video outputs	1 HDMI 4K, 1 VGA
Video compression format	Ultra H.265 / H.265 / H.264
Display resolution	3840x2160, 1920x1080, 1600x1200, 1280x1024, 1280x720, 1024x768
Total bandwidth	64 Mbps downstream / 48 Mbps upstream
Main Stream recording	4K / 5Mpx 4Mpx 3Mpx / 1080p / 960p 720p / D12CIF / CIF
Decoding	1x4K @ 30fps / 4x5MPx @ 25fps / 4x4MPx @ 25fps
Smart Intrusion Prevention	Available at 4 channels
Recording method	Manual, programmed, motion detection
External Backup	USB / HDD USB memory
Internal memory	1 SATA HDD 3.5" of up to 6 TB (not included)
Communication	2 x USB 2.0 / 1 x RJ45 (Ethernet)
Remote access	EZStation Web Browser, Smartphone App and PC Software
Power	DC 48 V
Dimensions / Weight	46(Al) x 260(An) x 240 (D) mm / 1Kg