



Tyyppi	Tuotenimi	A	D	E	F
EU140 - ilman varusteita					
EU14011	EU14011 IP44 TC-S 11W	335	178	190	58
EU14015	EU14015 IP44 T8 15W	475	273	400	44
EU14018	EU14018 IP44 T8 18W	628	196	503	63
EU141 - suojakumipäällysteinen kytkin					
EU14111	EU14111 IP44 TC-S 11W KYTKIN	335	178	190	58
EU14115	EU14115 IP44 T8 15W KYTKIN	475	273	400	44
EU14118	EU14118 IP44 T8 18W KYTKIN	628	196	503	63
EU142 - 2-os. pistorasia ja suojakumipääll. kytkin					
EU14211	EU14211 IP44 TC-S 11W 2-OS PR	521	364	190	245
EU14215	EU14215 IP44 T8 15W 2-OS PR	661	362	400	231
EU14218	EU14218 IP44 T8 18W 2-OS PR	814	365	480	231
EU142 - 2-os. pistorasia ja suojakumipääll. kytkin, harmaa					
EU14211H	EU14211H TC-S 11W 2-OS PR HA	521	364	190	245
EU14215H	EU14215H T8 15W 2-OS PR HA	661	362	400	231
EU14218H	EU14218H T8 18W 2-OS PR HA	814	365	480	231
EU142 - 2-os. pistorasia, suojakumipääll. kytkin, modulimitaiset (EU = valkoinen, EUH = harmaa)					
EU14229MOD	EU14229MOD IP44 TC-S2X9W 2 PR	597	392	296	244
EUH14229MOD	EUH14229MOD IP44 TC-S2X9W 2 PR	597	392	296	244
EU142 - 1-os. pistorasia, suojakumipääll. kytkin vikavirtasuojalla (EU = valkoinen, EUH = harmaa)					
EU14229V	EU14229V IP44 TC-S2X9W 1PR RCB	597	392	296	244
EU14229VH	EUH14229V TC-S2X9W 1PR RCB HA	597	392	296	244
EU143 - 1-os. pistorasia					
EU14314	EU14314 IP44 T5 14W 1-OS PR	670	260	500	125