



Main

Product or component type	Double socket-outlet
Device presentation	Mechanism
Outlet standard description	With earthing contact
Provided equipment	Sealing kit for flush IP44 mounting
Quantity per set	5 pieces

Complementary

Wiring device mounting	Semi-flush
Outlet poles configuration	2P + E with shutters
Rated current	16 A - 250 V AC
Colour tint	White
Connections - terminals	Screwless terminals
Number of loop terminals	1
Clamping connection capacity	1 x 1.5...2 x 2.5 mm ² solid cable(s) 1 x 1.5...2 x 2.5 mm ² solid stranded cable(s)
Material	PC
Fixing mode	By screw insert
Embedding depth	26 mm
Height	85 mm
Width	85 mm
Projecting depth	26 mm

Environment

standards	IEC 60884-1 SFS 5610:2004 SS 4280834 DIN VDE 0620-1
product certifications	FIMKO NEMKO SEMKO
IP degree of protection	IP44

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.