

**de** Montageanleitung  
\*) über Kundendienst erhältlich

**da** Monteringsvejledning  
\*) Kan købes hos serviceafdelingen

**sv** Monteringsanvisning  
\*) kan fås via Service

**no** Monteringsanvisning  
\*) fåes hos kundeservice

**fi** Asennusohje  
\*) Saatavissa huoltopalvelusta

9001 449 300 (9904)

GV 440 Unterbau SK + Sm Br-Sockel - Zeolith

**1**

1) L-shaped metal bracket  
2) Cable, 1,75 m  
3a) Screws, 4x28  
3b) Screws, 4x28  
4) Metal plate  
5) Metal plate  
6) Screws, Ø4x13 T  
7) Screws, Ø4x13 T  
8) Screws, Ø4x13 T  
9) Screws, Ø4x13 T  
10) Screws, Ø4x13 T  
11) Screws, Ø4x13 T

QR code

Dimensions: 815 - 860 mm, 845 - 880 mm, 570 mm, 815 - 875 mm, 450 (max. 458), 100x50mm

**2a**

Dimension: > 458

\*) Mat.-Nr. 10011641

**2b**

Dimension: 450 (max. 458)

5

**3**

QR code

nicht einklemmen  
klem ikke ind  
inte klämma fas  
ikke klem fast  
ei saa jäädä puristuksiin

6

**4**

0 - 60 mm

SW 13

SW 10

verspannen  
spænd  
spänna  
spenn fast  
tasapainota

QR code

**5**

QR code

