

# NOCTIS LUX 4

SLI029077CW\_PW

Floodlight NOCTIS LUX 4, with a power of 50 W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK07 class provides impact resistance. It shines with a cold light (6000K). Designed for surface mounting.

IP65

IK07



|                 |                       |
|-----------------|-----------------------|
| Power           | <b>50 W</b>           |
| Luminous flux*  | <b>4300 lm (120°)</b> |
| Colour of light | <b>CW</b>             |
| IK              | <b>7</b>              |

|                           |               |
|---------------------------|---------------|
| Voltage                   | <b>230 V</b>  |
| Colour temperature        | <b>6000 K</b> |
| Beam angle                | <b>100 °</b>  |
| Degree of protection (IP) | <b>IP65</b>   |

## Technical data

|                              |                |
|------------------------------|----------------|
| Code                         | SLI029077CW_PW |
| Power                        | 50 W           |
| Nominal current              | 215 mA         |
| Voltage                      | 230 V          |
| Energy consumption           | 50 kWh/1000h   |
| Frequency                    | 50HZ Hz        |
| Protection class             | I              |
| Power supply included        | +              |
| Power factor                 | 0.9            |
| Useful luminous flux*        | 4300 lm (120°) |
| Luminous flux                | 4300 lm (360°) |
| Lamp efficacy                | 86 lm/W        |
| Colour temperature           | 6000 K         |
| Colour of light              | CW             |
| Beam angle                   | 100 °          |
| RA                           | 70             |
| Light source included        | Yes            |
| Uniformity of color SDCM max | 5              |
| Dimmable                     | No             |
| Working temperature range    | -20/+40 °      |
| Warranty                     | 2 years        |
| Lifespan                     | 17000 h        |
| (On/Off)                     | 15000          |
| Housing material             | aluminum       |
| IK                           | 7              |
| Degree of protection (IP)    | IP65           |
| Colour                       | White          |
| Dimension (AxBxC)            | 176x137x25 mm  |
| For use                      | Outside        |
| Assembly method              | On the ceiling |
| Made in                      | PRC            |

## Logistics data

|                       |          |
|-----------------------|----------|
| Bulk packaging        | 20 pcs.  |
| Quantity per pallet   | 720 pcs. |
| Gross weight (1 pcs.) | 0.448 kg |

\*applies to the LED source used

## Related documents



 User manual



 Declaration of  
Conformity

