

NOCTIS LUX 4

SLI029077WW_CZUJNIK_PW

Floodlight NOCTIS LUX 4, with a power of 50 W. It has a high IP44 rating, making it ideal for use in areas of high humidity. IK07 class provides impact resistance. It shines with a warm light (3000K). Designed for surface mounting.

IP44

IK07



Power	50 W
Luminous flux*	4300 lm (120°)
Colour of light	WW
IK	7

Voltage	230 V
Colour temperature	3000 K
Beam angle	100 °
Degree of protection (IP)	IP44

Technical data

Code	SLI029077WW_CZUJNIK_PW
Power	50 W
Nominal current	215 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4300 lm (120°)
Luminous flux	4300 lm (360°)
Lamp efficacy	86 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	100 °
RA	70
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Housing material	aluminum
IK	7
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	176x221x53 mm
For use	Outside
Assembly method	On the ceiling
Made in	PRC
Other	PIR motion sensor ,

Logistics data

Bulk packaging	10 pcs.
Quantity per pallet	420 pcs.
Gross weight (1 pcs.)	0.544 kg

*applies to the LED source used

Related documents



 User manual



 Declaration of
Conformity

