

NOCTIS MAX CCT

SLI029082CCT_PW

NOCTIS MAX CCT FLOODLIGHT 20W CCT 230V IP65 175x134x28mm GREY 5Y WARRANTY



CCT

IP65

IK08



Power	20 W	Voltage	230 V
Luminous flux*	2000 lm (120°)	Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT	Beam angle	85 °
IK	8	Degree of protection (IP)	IP65

Technical data

Code	SLI029082CCT_PW
Power	20 W
Nominal current	80 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.93
Useful luminous flux*	2000 lm (120°)
Luminous flux	2000 lm (360°)
Lamp efficacy	100 lm/W
Luminous intensity	1300 cd
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	85 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum
IK	8
Degree of protection (IP)	IP65
Colour	Szary
Dimension (AxBxC)	175x134x28 mm
For use	Outside
Assembly method	On the ceiling
Other	Light color change function 3000K/4000K/6000K ,

Logistics data

Bulk packaging	40 pcs.
Quantity per pallet	960 pcs.
Gross weight (1 pcs.)	0.35 kg

*applies to the LED source used

Related documents



 User manual



 Declaration of
Conformity



 Photometric file

