

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
(Construction Products Regulation)

Nr. DoP-DE-tec 827 S

- Unique identification code of the product-type:*
weber.tec 827 S
RM P nach DIN EN 14891
- Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*
Batch/production date/production site/serial No. is printed on packaging or accompanying documents
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*
Reaction resin liquid-applied water impermeable product for external installations on walls and floors, beneath ceramic tiling resistant to contact with chlorinated water
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*
Saint-Gobain Weber GmbH
Schanzenstr. 84
D-40549 Düsseldorf
www.sg-weber.de
- Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*
not applicable
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*
AVCP System 3
- In case of the declaration of performance concerning a construction product covered by a harmonised standard:*
The notified testing laboratory Materialprüfanstalt für das Bauwesen Braunschweig (MPA), identification number No. 0761, performed the determination of the product-type on the basis of type testing under system 3 and issued: test report No. 5005/742/14-3.
- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*
not applicable

9. Declared performance

Essential characteristic	Performance	Harmonised technical specification
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	DIN EN 14891:2012-07
Water tightness	no penetration	
Crack bridging ability under standard conditions	$\geq 0,75 \text{ mm}$	
Tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$	
Tensile adhesion strength after water contact	$\geq 0,5 \text{ N/mm}^2$	
Tensile adhesion strength after contact with lime water	$\geq 0,5 \text{ N/mm}^2$	
Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$	
Release of dangerous substances	NPD	

NPD (No Performance Determined)

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Bruno Reisch, Direktor Technik

Düsseldorf, ... *May 30, 2014* ...
(Place and date of issue)

Bruno Reisch
.....
(Signature)

Annex

Material safety data sheet weber.tec 827 S, Comp. A

Material safety data sheet weber.tec 827 S, Comp. B