

# TORRE CCT

SLI003024CCT\_PW

LED luminaire TORRE CCT with the possibility of changing the light color (CCT), with a power of 18 W, high light efficacy 111 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 3000/4000/6000K, we can adjust the light color depending on our needs and preferences. It has a high IP54 rating, making it ideal for use in rooms with high humidity. The CCT function allows you to changes to the colour temperature of light (3000/4000/6000K). Narrow beam angle 30° gives directional light so that selected surfaces can be better exposed. Designed for surface mounting.

CCT

IP54

Power **18 W**Luminous flux\* **2000 lm (360°)**Colour of light **CCT**Degree of protection (IP) **IP54**Voltage **230 V**Colour temperature **3000/4000/6000 K**Beam angle **30 °**

## Technical data

---

|                           |                                                    |
|---------------------------|----------------------------------------------------|
| Code                      | SLI003024CCT_PW                                    |
| Power                     | 18 W                                               |
| Nominal current           | 135 mA                                             |
| Voltage                   | 230 V                                              |
| Energy consumption        | 18 kWh/1000h                                       |
| Frequency                 | 50HZ Hz                                            |
| Protection class          | II                                                 |
| Power factor              | 0.5                                                |
| Useful luminous flux*     | 2000 lm (360°)                                     |
| Luminous flux**           | 1400 lm (360°)                                     |
| Lamp efficacy             | 111 lm/W                                           |
| Colour temperature        | 3000/4000/6000 K                                   |
| Colour of light           | CCT                                                |
| Beam angle                | 30 °                                               |
| RA                        | 80                                                 |
| Light source included     | +                                                  |
| Dimmable                  | No                                                 |
| Working temperature range | -20/+40 °                                          |
| Lifespan                  | 17000 h                                            |
| Housing material          | Plastic                                            |
| Degree of protection (IP) | IP54                                               |
| Colour                    | Black                                              |
| Dimension (AxBxC)         | 99x78x162 mm                                       |
| For use                   | Inside/Outside                                     |
| Assembly method           | On the ceiling                                     |
| Application               | INT/EXT                                            |
| Made in                   | PRC                                                |
| Other                     | Light color change function<br>3000K/4000K/6000K , |

## Related documents

---



 User manual



 Declaration of Conformity



 Photometric file

