

# ENCANTA ASYMMETRIC

SLI003032CCT\_PW

LED luminaire ENCANTA ASYMMETRIC with the possibility of changing the light color (CCT), with a power of 6 W, high light efficacy 125 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 3000/4000/6000K, we can adjust the light color depending on our needs and preferences. It has a high IP54 rating, making it ideal for use in rooms with high humidity. The CCT function allows you to changes to the colour temperature of light (3000/4000/6000K). Designed for recessed mounting.

CCT

IP54

Power **6 W**Luminous flux\* **750 lm (360°)**Colour of light **CCT**Voltage **230 V**Colour temperature **3000/4000/6000 K**Degree of protection (IP) **IP54**

## Technical data

---

|                           |                                                    |
|---------------------------|----------------------------------------------------|
| Code                      | SLI003032CCT_PW                                    |
| Power                     | 6 W                                                |
| Nominal current           | 50 mA                                              |
| Voltage                   | 230 V                                              |
| Energy consumption        | 6 kWh/1000h                                        |
| Frequency                 | 50HZ Hz                                            |
| Protection class          | II                                                 |
| Power factor              | 0.5                                                |
| Useful luminous flux*     | 750 lm (360°)                                      |
| Luminous flux**           | 250 lm (360°)                                      |
| Lamp efficacy             | 125 lm/W                                           |
| Colour temperature        | 3000/4000/6000 K                                   |
| Colour of light           | CCT                                                |
| RA                        | 80                                                 |
| Light source included     | +                                                  |
| Dimmable                  | No                                                 |
| Working temperature range | -20/+40 °                                          |
| Lifespan                  | 17000 h                                            |
| Housing material          | PLASTIC                                            |
| Degree of protection (IP) | IP54                                               |
| Colour                    | Black                                              |
| Dimension (AxBxC)         | 230x84x60 mm                                       |
| Mounting hole             | 226x85x52 mm                                       |
| For use                   | Inside/Outside                                     |
| Assembly method           | Recessed                                           |
| Application               | INT/EXT                                            |
| Made in                   | PRC                                                |
| Other                     | Light color change function<br>3000K/4000K/6000K , |

## Related documents

---



 User manual



 Declaration of Conformity



 Photometric file

