

# STREETOS

SLI027014NW\_PW

Street luminaire STREETOS, with a power of 50 W, high light efficacy 152 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP66, providing protection against the ingress of dust and water jets. IK9 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K).



|                 |                       |
|-----------------|-----------------------|
| Power           | <b>50 W</b>           |
| Luminous flux*  | <b>7600 lm (360°)</b> |
| Colour of light | <b>Neutral white</b>  |
| IK              | <b>9</b>              |

|                           |                 |
|---------------------------|-----------------|
| Voltage                   | <b>230 V</b>    |
| Colour temperature        | <b>4000 K</b>   |
| Beam angle                | <b>130/80 °</b> |
| Degree of protection (IP) | <b>IP66</b>     |

## Technical data

|                              |                   |
|------------------------------|-------------------|
| Code                         | SLI027014NW_PW    |
| Power                        | 50 W              |
| Nominal current              | 220 mA            |
| Voltage                      | 230 V             |
| Energy consumption           | 50 kWh/1000h      |
| Frequency                    | 50HZ Hz           |
| Protection class             | I                 |
| Power factor                 | 0.9               |
| Useful luminous flux*        | 7600 lm (360°)    |
| Luminous flux**              | 7200 lm (360°)    |
| Lamp efficacy                | 152 lm/W          |
| Colour temperature           | 4000 K            |
| Colour of light              | Neutral white     |
| Beam angle                   | 130/80 °          |
| RA                           | 70                |
| Uniformity of color SDCM max | 5                 |
| Dimmable                     | No                |
| Working temperature range    | -20/+40 °         |
| Lifespan                     | 50000 h           |
| Housing material             | Aluminum, PLASTIC |
| IK                           | 9                 |
| Degree of protection (IP)    | IP66              |
| Colour                       | Gray              |
| Dimension (AxBxC)            | 455x122x77 mm     |
| Mounting hole                | 60 mm             |
| For use                      | Outside           |
| Assembly method              | On a pole         |
| Application                  | EXT               |
| Made in                      | PRC               |
| Other                        | 100-265V ,        |



## Related documents



 Declaration of Conformity



 Photometric file

