

NOCTIS LUX 2

SLI029044NW

Floodlight NOCTIS LUX 2, with a power of 50 W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. It shines with light of neutral - the most universal colour (4000K). Designed for surface mounting.

IP65



Power	50 W	Voltage	230 V
Luminous flux*	4000 lm (120°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	100 °
Degree of protection (IP)	IP65		

Technical data

Code	SLI029044NW
Power	50 W
Nominal current	230 mA
Voltage	230 V
Energy consumption	50 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4000 lm (120°)
Luminous flux**	3850/4000 lm (360°)
Lamp efficacy	77 lm/W
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	100 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, GLASS
Degree of protection (IP)	IP65
Colour	White
Dimension (AxBxC)	160x205x31 mm
For use	Inside/Outside
Assembly method	On the ceiling
Application	INT/EXT
Made in	PRC

Related documents



 Declaration of Conformity



 Photometric file

