

# NOCTIS LUX 3

SLI029055WW\_PW

Floodlight NOCTIS LUX 3, with a power of 50 W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK07 class provides impact resistance. It shines with a warm light (3000K). Designed for surface mounting.

IP65


IK07



|                 |                       |                           |               |
|-----------------|-----------------------|---------------------------|---------------|
| Power           | <b>50 W</b>           | Voltage                   | <b>230 V</b>  |
| Luminous flux*  | <b>4300 lm (120°)</b> | Colour temperature        | <b>3000 K</b> |
| Colour of light | <b>WW</b>             | Beam angle                | <b>100 °</b>  |
| IK              | <b>07</b>             | Degree of protection (IP) | <b>IP65</b>   |

## Technical data

|                              |                 |
|------------------------------|-----------------|
| Code                         | SLI029055WW_PW  |
| Power                        | 50 W            |
| Nominal current              | 220 mA          |
| Voltage                      | 230 V           |
| Energy consumption           | 50 kWh/1000h    |
| Frequency                    | 50HZ Hz         |
| Protection class             | I               |
| Power supply included        | +               |
| Power factor                 | 0.9             |
| Useful luminous flux*        | 4300 lm (120°)  |
| Luminous flux**              | 4300 lm (360°)  |
| Lamp efficacy                | 86 lm/W         |
| Colour temperature           | 3000 K          |
| Colour of light              | WW              |
| Beam angle                   | 100 °           |
| RA                           | >70             |
| Uniformity of color SDCM max | 5               |
| Dimmable                     | No              |
| Working temperature range    | -20/+40 °       |
| Lifespan                     | 17000 h         |
| Housing material             | Aluminum, GLASS |
| IK                           | 07              |
| Degree of protection (IP)    | IP65            |
| Colour                       | White           |
| Dimension (AxBxC)            | 180x140x27 mm   |
| For use                      | Outside         |
| Assembly method              | On the ceiling  |
| Application                  | EXT             |
| Made in                      | PRC             |



## Related documents

 Declaration of Conformity Photometric file

