

NYMPHEA

SLI031032CCT

Smart LED luminaire NYMPHEA with the possibility of changes to the colour temperature of light (CCT), with the possibility of dimming (DIMM) and remote commissioning and control via the app on your mobile device. Designed for surface mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

CCT



Power	36 W	Voltage	230 V
Luminous flux*	2840 lm (120°)	Colour temperature	2700-6500 K
Colour of light	CCT	Beam angle	120 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI031032CCT
Power	36 W
Nominal current	165 mA
Voltage	230 V
Energy efficiency class	F
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	2840 lm (120°)
Luminous flux**	2840 lm (360°)
Lamp efficacy	79 lm/W
Colour temperature	2700-6500 K
Colour of light	CCT
Beam angle	120 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	SMART
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	488x72 mm
For use	Inside
Assembly method	On the ceiling
Application	INT
Made in	PRC

Related documents



 User manual



 Declaration of Conformity



 Photometric file

