

# NYMPHEA

SLI031033CCT

Smart LED luminaire NYMPHEA with the possibility of changes to the colour temperature of light (CCT), with the possibility of dimming (DIMM) and remote commissioning and control via the app on your mobile device. Designed for surface mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

CCT



|                           |                       |                    |                    |
|---------------------------|-----------------------|--------------------|--------------------|
| Power                     | <b>24 W</b>           | Voltage            | <b>230 V</b>       |
| Luminous flux*            | <b>1840 lm (120°)</b> | Colour temperature | <b>2600-6000 K</b> |
| Colour of light           | <b>CCT</b>            | Beam angle         | <b>130 °</b>       |
| Degree of protection (IP) | <b>IP20</b>           |                    |                    |

## Technical data

---

|                           |                |
|---------------------------|----------------|
| Code                      | SLI031033CCT   |
| Power                     | 24 W           |
| Nominal current           | 110 mA         |
| Voltage                   | 230 V          |
| Energy efficiency class   | G              |
| Energy consumption        | 24 kWh/1000h   |
| Frequency                 | 50HZ Hz        |
| Protection class          | I              |
| Power factor              | 0.5            |
| Useful luminous flux*     | 1840 lm (120°) |
| Luminous flux**           | 1840 lm (360°) |
| Lamp efficacy             | 77 lm/W        |
| Luminous intensity        | 450 cd         |
| Colour temperature        | 2600-6000 K    |
| Colour of light           | CCT            |
| Beam angle                | 130 °          |
| RA                        | >80            |
| Light source included     | Yes            |
| Dimmable                  | Yes            |
| Working temperature range | -20/+40 °      |
| Lifespan                  | 17000 h        |
| Degree of protection (IP) | IP20           |
| Colour                    | White          |
| Dimension (AxBxC)         | 390x70 mm      |
| For use                   | Inside         |
| Assembly method           | On the ceiling |
| Made in                   | PRC            |
| Other                     | 2600-6000K ,   |

## Related documents

---



 Declaration of Conformity