

# NYMPHEA CITY PRO 2

SLI031039CCT\_PW

Plafond NYMPHEA CITY PRO 2 with the possibility of changing the light color (CCT), with power regulation on the power supply (18/24 W), high light efficacy 145 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 3000/4000/6000K, we can adjust the light color depending on our needs and preferences. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. The CCT function allows you to changes to the colour temperature of light (3000/4000/6000K). Designed for surface mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.

**CCT****IP65****IK08**

|                 |                       |
|-----------------|-----------------------|
| Power           | <b>18/24 W</b>        |
| Luminous flux*  | <b>3500 lm (360°)</b> |
| Colour of light | <b>CCT</b>            |
| IK              | <b>08</b>             |

|                           |                         |
|---------------------------|-------------------------|
| Voltage                   | <b>230 V</b>            |
| Colour temperature        | <b>3000/4000/6000 K</b> |
| Beam angle                | <b>120 °</b>            |
| Degree of protection (IP) | <b>IP65</b>             |

## Technical data

|                              |                                                 |
|------------------------------|-------------------------------------------------|
| Code                         | SLI031039CCT_PW                                 |
| Power                        | 18/24 W                                         |
| Nominal current              | 170 mA                                          |
| Voltage                      | 230 V                                           |
| Energy consumption           | 24 kWh/1000h                                    |
| Frequency                    | 50HZ Hz                                         |
| Protection class             | II                                              |
| Power supply included        | +                                               |
| Power factor                 | 0.65                                            |
| Useful luminous flux*        | 3500 lm (360°)                                  |
| Luminous flux**              | 1800/2400 lm (360°)                             |
| Lamp efficacy                | 145 lm/W                                        |
| Colour temperature           | 3000/4000/6000 K                                |
| Colour of light              | CCT                                             |
| Beam angle                   | 120 °                                           |
| RA                           | 80                                              |
| Light source included        | +                                               |
| Uniformity of color SDCM max | 5                                               |
| Dimmable                     | No                                              |
| Working temperature range    | -20/+40 °                                       |
| Lifespan                     | 50000 h                                         |
| Housing material             | PC                                              |
| IK                           | 08                                              |
| Degree of protection (IP)    | IP65                                            |
| Colour                       | White                                           |
| Dimension (AxBxC)            | 320x80 mm                                       |
| For use                      | Inside/Outside                                  |
| Assembly method              | On the ceiling                                  |
| Application                  | INT/EXT                                         |
| Made in                      | PRC                                             |
| Other                        | DIP SWITCH - adjustable<br>power of luminaire , |

## Related documents



 User manual



 Declaration of Conformity



 Photometric file

