

ANDROMEDA PRIME

SLI033035CCT_PW

On track luminaire ANDROMEDA PRIME with the possibility of changing the light color (CCT), with a power of 16 W, high light efficacy 109 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 2700/4000/6000K, we can adjust the light color depending on our needs and preferences. Narrow beam angle 25° gives directional light so that selected objects or surfaces can be better exposed. Designed to be mounted on a track.

CCT




Power	16 W
Luminous flux*	1750 lm (360°)
Colour of light	CCT
Degree of protection (IP)	IP20

Voltage	230 V
Colour temperature	2700/4000/6000 K
Beam angle	25 °

Technical data

Code	SLI033035CCT_PW
Power	16 W
Nominal current	120 mA
Voltage	230 V
Energy consumption	16 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.5
Useful luminous flux*	1750 lm (360°)
Luminous flux**	1200 lm (360°)
Lamp efficacy	109 lm/W
Luminous intensity	5900 cd
Colour temperature	2700/4000/6000 K
Colour of light	CCT
Beam angle	25 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
Degree of protection (IP)	IP20
Colour	Black
Dimension (AxBxC)	63x134x184 mm
For use	Inside/Outside
Assembly method	on track
Application	Inside
Made in	PRC
Other	Light color change function 2700K/4000K/6000K ,



Related documents

 User manual Declaration of Conformity Photometric file 3D model

