

ALGINE BACKLIGHT

SLI035055WW_PW

LED panel ALGINE BACKLIGHT, with a power of 30 W, high light efficacy 137 lm/W. It is made of high-quality components, supported by a 5-year warranty. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	30 W	Voltage	230 V
Luminous flux*	4100 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	120 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI035055WW_PW
Power	30 W
Nominal current	132 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	4100 lm (360°)
Luminous flux**	3400 lm (360°)
Lamp efficacy	137 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Steel/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x28 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC



Related documents



 User manual



 Declaration of Conformity



 Photometric file

