

ALGINE BACKLIGHT

SLI035066WW_PW

LED panel ALGINE BACKLIGHT, with a power of 40 W, high light efficacy 135 lm/W. It is made of high-quality components, supported by a 5-year warranty. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Suitable for both surface and recessed mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.



Power	40 W	Voltage	230 V
Luminous flux*	5400 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	120 °
UGR	<19	Degree of protection (IP)	IP20

Technical data

Code	SLI035066WW_PW
Power	40 W
Nominal current	185 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	+
Power factor	0.9
Useful luminous flux*	5400 lm (360°)
Luminous flux**	4400 lm (360°)
Lamp efficacy	135 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
UGR	<19
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum/Plastic
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x32 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Made in	PRC

Related documents



 User manual



 Declaration of Conformity



 Photometric file

