

PLATEO SUN 3

SLI044031NW_PW

High bay luminaire PLATEO SUN 3, with a power of 200 W, high light efficacy 110 lm/W. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. It shines with light of neutral - the most universal colour (4000K). Narrow beam angle 90° gives directional light so that selected surfaces can be better exposed. Designed for suspended mounting.

IP65

IK06



Power	200 W	Voltage	230 V
Luminous flux*	22050 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	90 °
IK	06	Degree of protection (IP)	IP65

Technical data

Code	SLI044031NW_PW
Power	200 W
Nominal current	870 mA
Voltage	230 V
Energy consumption	200 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.9
Useful luminous flux*	22050 lm (360°)
Luminous flux**	20000 lm (360°)
Lamp efficacy	110 lm/W
Luminous intensity	8700 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	90 °
RA	>80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Lifespan	17000 h
Housing material	Aluminum/PC
IK	06
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	309x68 mm
For use	Outside
Assembly method	Suspended
Application	Outside
Made in	PRC

Related documents



 Declaration of Conformity