

# VIGA

SLI045004WW\_PW

Linear luminaire VIGA, with a power of 28 W, high light efficacy 114 lm/W. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Suitable for both surface and suspended mounting.



---

Power	<b>28 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>3200 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>120 °</b>
Degree of protection (IP)	<b>IP20</b>		

---

## Technical data


---

Code	SLI045004WW_PW
Power	28 W
Nominal current	140 mA
Voltage	230 V
Energy consumption	28 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.9
Useful luminous flux*	3200 lm (360°)
Luminous flux**	2600 lm (360°)
Lamp efficacy	114 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	120 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	76x1200x26 mm
For use	Inside
Assembly method	On the ceiling, Suspended
Application	INT
Made in	PRC


## Related documents

---



 Declaration of Conformity



 Photometric file