

LIMEA SUBTILO

SLI047220CCT_PW

LED luminaire LIMEA SUBTILO with the possibility of changing the light color (CCT), with a power of 15 W, high light efficacy 120 lm/W. Thanks to the ability to change the color temperature (CCT) in the range 2700/4000/6000K, we can adjust the light color depending on our needs and preferences. Suitable for both surface and suspended mounting. The product is certified by the National Institute of Hygiene, so it can be used in rooms with high hygienic requirements.


CCT



Power	15 W	Voltage	230 V
Luminous flux*	1800 lm (360°)	Colour temperature	2700/4000/6000 K
Colour of light	CCT	Beam angle	120 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI047220CCT_PW
Power	15 W
Nominal current	115 mA
Voltage	230 V
Energy consumption	15 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.55
Useful luminous flux*	1800 lm (360°)
Luminous flux**	1500 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	2700/4000/6000 K
Colour of light	CCT
Beam angle	120 °
RA	80
Light source included	+
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	PLASTIC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	600x60x35 mm
For use	Inside
Assembly method	On the ceiling, Suspended
Application	INTERNAL
Made in	PRC
Other	Light color change function 2700K/4000K/6000K ,



Related documents



 User manual



 Declaration of Conformity



 Photometric file

