

HALLS LINE

SLI048003NW_PW


High bay luminaire HALLS LINE, with a power of 150 W, high light efficacy 153 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP66, providing protection against the ingress of dust and water jets. IK10 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Designed for suspended mounting.



Power	150 W	Voltage	230 V
Luminous flux*	23000 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	75x140 °
IK	10	Degree of protection (IP)	IP66

Technical data

Code	SLI048003NW_PW
Power	150 W
Nominal current	670 mA
Voltage	230 V
Energy consumption	150 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.95
Useful luminous flux*	23000 lm (360°)
Luminous flux**	21000 lm (360°)
Lamp efficacy	153 lm/W
Luminous intensity	11000 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	75x140 °
RA	>80
Light source included	Yes
Dimmable	Yes
Working temperature range	-20 +40 °
Lifespan	50000 h
Housing material	Aluminum
IK	10
Degree of protection (IP)	IP66
Colour	Black
Dimension (AxBxC)	745x126x95 mm
For use	Outside/Inside
Assembly method	Suspended
Whether it should work in conditions other than normal	Yes
Made in	PRC



Related documents



 User manual



 Declaration of Conformity



 Photometric file

