

HALLS LINE 2

SLI048008NW_PW

High bay luminaire HALLS LINE 2, with a power of 150 W, high light efficacy 155 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP66, providing protection against the ingress of dust and water jets. IK10 class provides impact resistance. It shines with light of neutral - the most universal colour (4000K). Designed for suspended mounting.



IP66

IK10



Power	150 W
Luminous flux*	23250 lm (360°)
Colour of light	Neutral white
IK	10

Voltage	230 V
Colour temperature	4000 K
Beam angle	60x90 °
Degree of protection (IP)	IP66

Technical data

Code	SLI048008NW_PW
Power	150 W
Nominal current	665 mA
Voltage	230 V
Energy consumption	150 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power supply included	Yes
Power factor	0.95
Useful luminous flux*	23250 lm (360°)
Luminous flux**	22500 lm (360°)
Lamp efficacy	155 lm/W
Luminous intensity	22350 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	60x90 °
RA	80
Light source included	Yes
Dimmable	Yes
Working temperature range	-20 +40 °
Lifespan	50000 h
Housing material	Aluminum
IK	10
Degree of protection (IP)	IP66
Colour	Black
Dimension (AxBxC)	900x150x130 mm
For use	Outside/Inside
Assembly method	Suspended
Whether it should work in conditions other than normal	Yes
Made in	PRC
Other	Zaw. 2 źródła św. o EEI D, Fi use=11625lm, P=75W ,

Related documents



 User manual



 Declaration of Conformity



 Photometric file

