

# LED STRIP

W0J+14405

LED strip LED STRIP 24(5.6) W in silicone cover. It has a high IP44 rating, making it ideal for use in rooms with high humidity. It also stands out for its very high colour rendering index RA>90. It shines with a cold light colour (6000K), which is suitable for rooms where we need to be most focused and concentrated, such as technical workstations.

**IP44**

|                           |                       |                    |               |
|---------------------------|-----------------------|--------------------|---------------|
| Power                     | <b>24(5.6) W</b>      | Voltage            | <b>12 V</b>   |
| Luminous flux**           | <b>2200 lm (360°)</b> | Colour temperature | <b>6000 K</b> |
| Colour of light           | <b>CW</b>             | Beam angle         | <b>120 °</b>  |
| Degree of protection (IP) | <b>IP44</b>           |                    |               |

## Technical data

---

|                              |                |
|------------------------------|----------------|
| Code                         | W0J+14405      |
| Power                        | 24(5.6) W      |
| Nominal current              | 2000 mA        |
| Voltage                      | 12 V           |
| Energy efficiency class      | G              |
| Energy consumption           | 24 kWh/1000h   |
| Frequency                    | DC Hz          |
| Power factor                 | 1              |
| Luminous flux**              | 2200 lm (360°) |
| Lamp efficacy                | 92 lm/W        |
| Colour temperature           | 6000 K         |
| Colour of light              | CW             |
| Beam angle                   | 120 °          |
| RA                           | 90             |
| Uniformity of color SDCM max | 5              |
| Dimmable                     | Yes            |
| Working temperature range    | -20/+40 °      |
| Lifespan                     | 17000 h        |
| Degree of protection (IP)    | IP44           |
| Dimension (AxBxC)            | 8X5000 mm      |
| For use                      | Inside/Outside |
| Application                  | INT/EXT        |
| Made in                      | PRC            |

## Related documents

---



 Declaration of Conformity