

# LED G4

WOJ+14430

LED source LED G4 2,5 W. It is perfect for use in households, hotels, shops, or restaurants as decorative or accent lighting, and can be installed in luminaires that have a G4 base. It is characterised by a high light efficacy 108 lm/W. It is made of high-quality components, supported by a 5-year warranty. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Wide beam angle 270° ensures even illumination of the room.



Power	<b>2,5 W</b>	Voltage	<b>12 V</b>
Luminous flux**	<b>270 lm (360°)</b>	Colour temperature	<b>3000 K</b>
Colour of light	<b>WW</b>	Beam angle	<b>270 °</b>
Socket	<b>G4</b>		

## Technical data


---

Code	W0J+14430
Power	2,5 W
Nominal current	300 mA
Voltage	12 V
Energy efficiency class	F
Energy consumption	3 kWh/1000h
Frequency	50HZ Hz
Useful luminous flux*	270 lm (360°)
Luminous flux**	270 lm (360°)
Lamp efficacy	108 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	270 °
RA	80
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Socket	G4
Dimension (AxBxC)	ø13x45 mm
For use	N,A
Made in	PRC

## Related documents

---



 Declaration of Conformity